PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2001-117058

(43)Date of publication of application: 27.04.2001

(51)Int.CI.

G02F 1/025 G02B 6/12

// H01S 5/22

(21)Application number: 11-291890

(71)Applicant: OKI ELECTRIC IND CO LTD

(22)Date of filing:

14.10.1999


(72)Inventor: YAMADA MITSUSHI

(54) SEMICONDUCTOR WAVEGUIDE ELEMENT AND METHOD FOR MANUFACTURING THE SAME

(57)Abstract:

PROBLEM TO BE SOLVED: To provide a semiconductor waveguide element having large permissible input light power.

SOLUTION: An upper clad layer 40 of the semiconductor waveguide element, which has a lower clad layer 20, the upper clad layer 40, an optical waveguide layer 30 held therebetween, a lower electrode 80 and an upper electrode 70 and makes light incident on the optical waveguide layer 30 from its end face, has striped narrow—width portions 41 and a broad—width portion 42 which is formed in a position nearer the end face made incident with the light than these narrow—width portions 41 and has a width broader than the width of the narrow—width portions 41.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]